

VISCOUNT RECRATE RANGE



Viscount Plastics Recrate range of crates are suitable for almost all transport requirements. Viscount have consulted with a variety of industries to find solutions that fit with process, cost and transport needs, and have custom moulded crates to suit.

The unit loads are indicative only, all sizes of crate carry up to 22kg, provided maximum load bottom crate does not exceed 180kg.

Please consult Viscount Plastics where weights, volumes and dimensions are critical, as those shown should be treated as indicative only. (Viscount Plastics reserves the right to make product alterations at its discretion).



Auckland
8 Vestey Drive,
Mt Wellington
PO Box 22462, Otahuhu
Auckland, New Zealand
Tel: +64 9 276 8679
Fax: +64 9 276 4392

Wellington
Level 2, 46-50
Bloomfield Terrace
PO Box 30238, Lower Hutt,
Wellington, New Zealand
Tel: +64 4 570 3328
Fax: +64 4 570 3329

Christchurch
Cnr Brougham &
Gasson Streets
PO Box 7111,
Christchurch, New Zealand
Tel: +64 3 365 4382
Fax: +64 3 366 6026

RECRATE RANGE

www.viscountplastics.co.nz

TECHNICAL SPECIFICATIONS

	Recrate 25	Recrate 35	Recrate 47	Recrate 75
External dimensions (mm)	600, 400, 140	600, 400, 193	600, 400, 247	600, 400, 395
Internal dimensions (mm)	549, 348, 118	549, 348, 161	549, 348, 221	549, 348, 368
Incremental nest height (mm)	62	97	118	150
Incremental stack height (mm)	134	182	240	388
Product weight (kg) (including stacking bars)	1.44	1.64	1.97	2.91
Unit load (kg)	12	15	18	22
Maximum load (kg)	180	180	180	180
Stack height (maximum recommended)	15	12	10	8
Capacity (litres)	25	35	47	75

Feature

100% Plastic

Nesting

Strapping Lugs

600mm x 400mm Dimensions

Produce-caring ventilation pattern

Fully radiused edges

Completely smooth interior

Smooth exterior base

Stacking bar channels

Permanent branding options

Label holders

Four handle holds

Colour options available

Food grade material

Benefit

No splinters, no rusting, more hygienic, easily cleaned, light weight

Maximum freight efficiency for empty crates
Tapered sides ensure easy de-nesting

Allows simple and easy load stabilisation

Internationally recognised as maximising usable space on standard 1200mm x 1000mm pallets

Small size vent slots prevent produce damage, while the large number of vents allows maximum air flow through contents

No sharp corners on the inside or outside to damage contents or crate handlers

Makes the most of internal space with no protrusions to damage contents

No protruding edges to damage contents in crate below

Ensures a positive locking system when crates are stacked on top of the other

Either moulded or hot stamped into the crate
Room for logo and message

Easily seen user information or inventory labelling

Provides maximum flexibility and comfort for handling crates

Allows for colour identification
Availability depends on quantities ordered

Polypropylene suitable for food contact use

RECRATE RANGE

www.viscountplastics.co.nz